

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A method comprising:
receiving, by an application executed by an operating system, an operating parameter of a client device;
~~assigning~~ changing a value representing a performance measure of the client device
assigned to a usage variable ~~associated with~~ based at least in part on the
operating parameter of the client device; and
correlating by ~~[[an]]~~ the application a resource usage level of the application with the
usage variable, the correlating comprising the application modifying its own
execution based at least in part on the change to the value assigned to the
usage variable.
2. (Currently amended) The method of claim 1, wherein correlating by the application
the resource usage level of the application with the usage variable comprises the application
suspending one or more operations when the value assigned to the usage variable exceeds a
threshold.
3. (Currently amended) The method of claim 1, wherein correlating by the application
the resource usage level of the application with the usage variable comprises the application
performing an activity affecting a usage variable proximate to a time that the value assigned to
the usage variable indicates an existing activity.
4. (Currently amended) The method of claim 1, wherein correlating by the application
the resource usage level of the application with the usage variable comprises the application
adjusting a rate of operation based at least in part on the value assigned to the usage variable.
5. (Currently amended) The method of claim 1, wherein correlating by an application
the resource usage level of the application with the usage variable comprises the application

adjusting a sequence of operations based at least in part on the value assigned to the usage variable.

6. (Currently amended) The method of claim 1, wherein correlating by the application the resource usage level of the application with the usage variable comprises the application adjusting an active feature based at least in part on the value assigned to the usage variable.

7. (Original) The method of claim 1, wherein the client device comprises a client processor and a client memory storage device.

8. (Original) The method of claim 1, wherein receiving the operating parameter comprises monitoring the operating parameter.

9. (Original) The method of claim 7, further comprising monitoring a period of inactivity of the client device.

10. (Original) The method of claim 7, wherein receiving the operating parameter comprises receiving the operating parameter during an initial load of the client processor.

11. (Original) The method of claim 7, wherein receiving the operating parameter comprises receiving the operating parameter during a predetermined time interval.

12. (Original) The method of claim 11, wherein the operating parameter comprises a client processor load.

13. Canceled.

14. Canceled.

15. (Original) The method of claim 7, further comprising writing to a computer readable medium of the client memory storage device.

16. (Original) The method of claim 10, wherein the operating parameter comprises a first parameter and a second parameter, the first parameter comprising a speed of the client processor and the second parameter comprising a capacity of the client memory storage device.

17. (Currently amended) A computer readable storage medium comprising instructions, that, when executed, cause an application to perform the steps of:

receiving, by an application executed by an operating system, an operating parameter of a client device;

~~assigning~~ changing a value representing a performance measure of the client device assigned to a usage variable ~~associated with~~ based at least in part on the operating parameter of the client device; and

correlating by ~~[[an]]~~ the application a resource usage level of the application with the usage variable, the correlating comprising the application modifying its own execution based at least in part on the change to the value assigned to the usage variable.

18. (Currently amended) The computer readable medium of claim 17, wherein correlating the resource usage level of the application with the usage variable comprises the application suspending one or more operations when the value assigned to the usage variable exceeds a threshold.

19. (Currently amended) The computer readable medium of claim 17, wherein correlating the resource usage level of the application with the usage variable comprises the application performing an activity affecting a usage variable proximate to a time that the value assigned to the usage variable indicates an existing activity.

20. (Currently amended) The computer readable medium of claim 17, wherein correlating the resource usage level of the application with the usage variable comprises the application adjusting a rate of operation based at least in part on the value assigned to the usage variable.

21. (Currently amended) The computer readable medium of claim 17, wherein correlating the resource usage level of the application with the usage variable comprises the application adjusting a sequence of operations based at least in part on the value assigned to the usage variable.

22. (Currently amended) The computer readable medium of claim 17, wherein correlating the resource usage level of the application with the usage variable comprises the application adjusting an active feature based at least in part on the value assigned to the usage variable.

23. (Original) The computer readable medium of claim 17, wherein the client device comprises a client processor and a client memory storage device.

24. (Original) The computer readable medium of claim 17, further comprising instructions, that, when executed, cause the application to perform the step of monitoring a period of inactivity of the client device.

25. (Original) The computer readable medium of claim 23, wherein receiving the operating parameter comprises receiving the operating parameter during an initial load of the client processor.

26. (Original) The computer readable medium of claim 23, wherein receiving the operating parameter comprises receiving the client processor during a predetermined time interval.

27. (Original) The computer readable medium of claim 26, wherein the operating parameter comprises a client processor load.

28. Canceled.

29. Canceled.

30. (Original) The computer readable medium of claim 23, further comprising instructions, that, when executed, cause the application to perform the step of writing to a computer readable medium of the client memory storage device.

31. (Original) The computer readable medium of claim 25, wherein the operating parameter comprises a first parameter and a second parameter, the first parameter comprising a speed of the client processor and the second parameter comprising a capacity of the client memory storage device.

32. (Original) The computer readable medium of claim 30, wherein receiving the operating parameter comprises monitoring the operating parameter.

33. (New) The method of claim 1, wherein the usage variable is a quantitative performance measure of the client device.

34. (New) The method of claim 1, wherein the usage variable is a qualitative performance measure of the client device.

35. (New) The method of claim 1, wherein the application modifying its own execution comprises the application throttling back its usage of the client device.

36. (New) The method of claim 1, wherein the application dynamically modifies its own execution based on dynamic changes to the value assigned to the usage variable.

37. (New) The method of claim 1, wherein the application modifying its own execution comprises the application pausing between execution of resource-intensive calculations.

38. (New) The method of claim 1, wherein a resource used by the application is memory and wherein the application modifying its own execution comprises the application dynamically scaling back its memory usage based on dynamic changes to the value assigned to the usage variable.

39. (New) The method of claim 1, wherein a resource used by the application is network bandwidth and wherein the application modifying its own execution comprises the application throttling-back usage of network bandwidth based on dynamic changes to the value assigned to the usage variable.

40. (New) The method of claim 1, wherein the correlating further comprises:
examining a table having a column representing the usage variable and a column representing the resource usage level of the application and rows specifying values of the usage variable and resource usage levels;
identifying a row of the table matching the value assigned to the usage variable; and
modifying the execution of the application to use a level of resources specified by the identified row.

41. (New) The method of claim 1, wherein there are a plurality of usage variables and wherein the correlating comprises the application modifying its own execution based at least in part on changes to values assigned to the plurality of usage variables.